



### Tumble Dryers

#### Tumble Dryers Economic Line

## TUMBLE DRYER, SC-16 E ECONOMIC LINE

### DIMENSIONS

|         |    | Article  | Packed   |
|---------|----|----------|----------|
| Length  | mm | 785,00   | 880,00   |
| Depth   | mm | 1.110,00 | 1.225,00 |
| Height  | mm | 1.694,00 | 1.840,00 |
| Weigth  | Kg | 190,00   | 225,00   |
| Volumen | m3 |          | 1,98     |

### ELECTRICITY

| Electric power | KW |               |
|----------------|----|---------------|
| 230V -1+N      |    | NO            |
| 230V - III     |    | 3x16+T - 80 A |
| 400V - III+N   |    | 4x6+T - 50 A  |

### WATER

Not used

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### LEVEL SOUND

(dB) 64,00

### TUMBLE DRYER, SC-16 E ECONOMIC LINE

Load Capacity : 18 kg. (load factor 1:18) or 15 kg (load factor 1:22).

Production: + 33 kg/h.

Galvanized steel body.

Axial airflow.

Time selector.

Temperature selector.

COOL DOWN at end of cycle.

Lamp indicator ON and HEATING.

Open door with safety device.

EMERGENCY stop button.

Frecuency speed variator.

Alarm noise indicator at end of cycle.

Air extraction volume: 870 m3/h.

Drum in galvanized steel.

IMPORTANT: Reversing drum .

Drum diameter: 750 mm

Depth of drum: 746 mm

Diameter of door: 574 mm.

reversible door hanging.

Fluff filter in lower part .

Transmission by means of motoreducer .

Main heating system: electric

Electrical connection : 400 V - III+N+ GROUND - 50/60 Hz.

Heating power: 18 kW

Total power: 18,55 kW.

Dimensions: 785 x 1.110 x 1.694 mm

| Connections points | X   | Y | Z   | Diameter | Information |
|--------------------|-----|---|-----|----------|-------------|
| ELECTRICITY        | 528 | 0 | 821 |          | 0           |
| EXHAUST            | 558 | 0 | 169 | 200 mm.  |             |

