



**Ironers & Flatwork Ironers**

**Ironers**

**IRONER, PE-25/120 M**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>1.600,00</b>	<b>1.680,00</b>
Depth	mm	<b>405,00</b>	<b>500,00</b>
Height	mm	<b>1.005,00</b>	<b>1.180,00</b>
Weigth	Kg	<b>120,00</b>	<b>132,00</b>
Volumen	m3	<b>0,65</b>	<b>1,00</b>

**ELECTRICITY**

<u>Electric power</u>		<u>Article</u>	<u>Packed</u>
230V -1+N	KW		<b>6,18</b>
230V - III		<b>3x2,5+T-20A</b>	<b>NO</b>
400V - III+N		<b>4x1,5+T-16A</b>	

**WATER**

Not used

**GAS**

Not used

**STEAM**

Not used

**AIR**

Not used

**LEVEL SOUND**

(dB) **55,00**

**IRONER, PE-25/120 M**

Outer casing of varnished steel, white colour.  
 Roller coated in Polyester.  
 Works by means of a pedal.  
 Strap feeding.  
 Return feed design requires minimum installation space.  
 Safety protector for hands.  
 Controlled by microprocessor.  
 Temperature control by thermostat.  
 Safety thermostat.  
 Electric heating system.  
 Roller diameter Ø 250 mm.  
 Roller length: 1.200 mm.  
 Speed: 4,20 m/minute.  
 Production: 35 kg/h.  
 Electrical connection: 400 V 3+N.  
 Heating power: 6 kW.  
 Electrical power: 6,18 kW.  
 Dimensions: 1600 x 405 x 1005 mm.

Entry with 20% ÷ 25% maximum humidity

<u>Connections points</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameter</u>	<u>Information</u>
ELECTRICITY	80	0	765		0

