



Ironers & Flatwork Ironers

Flatwork ironers Ø 35

FLATWORK IRONER, PSE-35/140 MP

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	1.942,00	0,00
Depth	mm	660,00	0,00
Height	mm	1.112,00	0,00
Weigth	Kg	480,00	490,00
Volumen	m3	1,43	2,54

<u>ELECTRICITY</u>			
<u>Electric power</u>		KW	12,50
230V -1+N			NO
230V - III		OPT- 3x10+T-32A	
400V - III+N		4x4+T - 20 A	

WATER
Not used

GAS
Not used

STEAM Not used

AIR Not used

<u>LEVEL SOUND</u>	(dB)	60,00
--------------------	------	-------

FLAT WORK IRONER, PSE-35/140 MP
 Outer casing of white varnished steel.
 Return feed design requires minimum installation space.
 Steel roller.
 Strap feeding.
 NOMEX ironing straps.
 High throughput as linen is in contact with cylinder through a high proportion of the roller circumference.
 Safety protector for hands.
 Temperature control thermostat.
 Production: 10 / 16 kg/h.
 Roller length: 1.400 mm.
 Roller diameter: 325 mm.
 Ironing speed: 1 - 6,5 m/min.
 Ironing speed regulated by frequency variator.
 Temperature and speed MICROPROCESSOR CONTROL.
 Self auto diagnostic control.
 Automatic STOP by thermostat when roller is below 80 °C.
 HI -LIMIT safety thermostat.
 Exhaust sistem incorporated: 1 x 500 m3/h.
 Electric heating system.
 Heating power: 12 kW.
 Maximum power: 12,5 kW.
 Power intake: 400 V - III+N+T - 50 Hz.
 Dimensions: 1,942 x 660 x 1,112 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	1.872	0	130		0
EXHAUST	60	58	1.112	98	

